



US009452782B1

(12) **United States Patent**
Singer

(10) **Patent No.:** **US 9,452,782 B1**

(45) **Date of Patent:** **Sep. 27, 2016**

- (54) **PICK UP TRUCK ELONGATOR**
- (71) Applicant: **Nicholas J. Singer**, Irvine, CA (US)
- (72) Inventor: **Nicholas J. Singer**, Irvine, CA (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: **14/959,259**
- (22) Filed: **Dec. 4, 2015**
- (51) **Int. Cl.**
B62D 21/00 (2006.01)
B62D 21/14 (2006.01)
- (52) **U.S. Cl.**
CPC **B62D 21/14** (2013.01)
- (58) **Field of Classification Search**
CPC B62D 21/14
USPC 296/26.11, 26.08
See application file for complete search history.

6,367,858 B1	4/2002	Bradford	
6,378,926 B1	4/2002	Renze et al.	
6,422,630 B1	7/2002	Heaviside	
6,513,850 B1	2/2003	Reed	
6,550,841 B1	4/2003	Burdon et al.	
6,676,182 B2	1/2004	Fitts	
D504,384 S	4/2005	Straschewski	
6,908,134 B1	6/2005	Summers	
6,918,624 B2	7/2005	Miller et al.	
6,994,363 B2	2/2006	Seksaria et al.	
7,021,689 B1	4/2006	Weisbeck, III	
7,111,886 B1 *	9/2006	Miller	B60P 3/40 296/26.11
7,204,537 B1	4/2007	Oh et al.	
7,488,021 B1 *	2/2009	Roos	B60P 3/40 296/26.11
8,109,552 B2	2/2012	Nelson	
8,182,012 B1	5/2012	Brister	
2002/0000732 A1	1/2002	Sanders	
2002/0140244 A1	10/2002	Kuhn et al.	
2006/0214449 A1	9/2006	Klusmeier	
2010/0078955 A1	4/2010	Smith	
2012/0228893 A1	9/2012	Lu et al.	

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,872,239 A	2/1959	Bowness et al.
4,472,639 A	9/1984	Bianchi
4,531,773 A	7/1985	Smith
4,596,417 A	6/1986	Bennett
5,154,470 A	10/1992	Bringman, Jr.
5,244,335 A	9/1993	Johns
5,456,511 A	10/1995	Webber
5,468,038 A	11/1995	Sauri
5,669,654 A	9/1997	Eilers et al.
5,755,480 A	5/1998	Bryan
5,775,759 A	7/1998	Cummins
5,788,311 A	8/1998	Tibbals
5,857,724 A	1/1999	Jarman
5,924,753 A	7/1999	DiBassie
5,997,066 A	12/1999	Scott
6,019,410 A	2/2000	Trostle et al.
6,179,360 B1	1/2001	Davian
6,193,294 B1	2/2001	Disner et al.
6,279,980 B1	8/2001	Straschewski
6,340,190 B1	1/2002	Rosebrugh et al.

FOREIGN PATENT DOCUMENTS

CA	1244858 A1	11/1988
DE	814244 C	9/1951

* cited by examiner


Primary Examiner — Joseph D Pape

(74) *Attorney, Agent, or Firm* — Stetina Brunda Garred & Brucker

(57) **ABSTRACT**

A replacement tailgate for the purpose of elongating the pickup truck may be installed on a truck bed wherein the replacement tailgate can be unfolded in order to elongate a length of the truck bed. The replacement tailgate may have front and rear shells that are used to support objects placed in the truck bed as well as act as the new tailgate when the truck bed length is elongated. Various panels may be unfolded in order to trap objects within the truck bed when the replacement tailgate is unfolded in order to elongate the truck bed length.

7 Claims, 20 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12





FIG. 13






FIG. 15







FIG. 16










FIG. 20

1

PICK UP TRUCK ELONGATORCROSS-REFERENCE TO RELATED
APPLICATIONS

Not Applicable

STATEMENT RE: FEDERALLY SPONSORED
RESEARCH/DEVELOPMENT

Not Applicable

BACKGROUND

The various embodiments and aspects described herein relate to an accessory for a truck bed to elongate a length of the truck bed.

Trucks have beds that come in a variety of sizes. By way of example and not limitation, the truck beds may be a short bed or long bed. The short bed may serve the purposes of its owner a majority of the time but at certain times, the owner may require a slightly longer truck bed to haul larger or longer objects. In this regard, the owner may let down his or her tailgate and allow the objects to hang out of the back side of the truck bed when hauling the long object. In doing so, the object becomes a safety hazard in that other vehicles and pedestrians may not see the elongated object hanging out of the truck bed and may inadvertently hit the object causing injury to the person and/or damage to the object.

Additionally, the objects configuration may not be conducive to easily tying the object down in the truck bed. The tailgate is typically lifted upward in order to trap the object within the truck bed so that even if the object slides in the truck bed, the object would still remain within the truck bed.

Accordingly, there is a need in the art for an accessory for a truck bed.

BRIEF SUMMARY

A pickup truck elongator in the form of the tailgate is disclosed herein. The factory tailgate may be replaced with a replacement tailgate that can be pivoted downward to elongate the length of the factory truck bed. The replacement tailgate has a front shell that can be pivoted upward to function as the new tailgate when a rear shell of the replacement tailgate acts as the support to elongate the length of the factory truck bed. Left and right side panels may be unfolded in order to form an enclosure with left and right side walls of the truck bed. Additionally, the rear shell can be fabricated from first and second telescoping panels that allow the user to further expand the factory truck bed.

Alternatively, the original tailgate or replacement tailgate may act as the support to elongate the length of the factory truck bed. Side panels are tucked away in the cavity adjacent a rear side of the left and right truck side bed walls. The panels are folded out and engaged to the upper surface of the tailgate in order to retain objects placed in the truck bed within the truck bed.

More particularly, a tailgate for a bed of a truck is disclosed. The tailgate may comprise a rear shell, a front shell, left and right side panels and left and right latches. The rear shell may be sized and configured to fit between left and right sidewalls of the truck bed. The rear shell may be pivotally attached to a lower rear edge of the truck bed. The front shell may be pivotally attached to an upper edge of the rear shell. The front shell may be pivoted greater than 180 degrees when the front shell is disposed generally parallel to the rear

2

shell. The left and right side panels may be pivotally attached to left and right side portions of the front shell. The left and right latches may be attached to the left and right side panels and the left and right sidewalls of the truck bed to mitigate unwanted movement of the rear shell, front shell and the left and right panels during forward movement of the truck.

The rear shell may comprise first and second telescoping panels for elongating a length of the bed of the truck. The first and second telescoping panels may be attached to each other as a tongue and groove connection.

The tailgate may further comprise left and right elongating side panels which may be pivotally attached to respective ones of the left and right side panels. The left and right latches may be attached to the left and right elongating side panels and the left and right side walls of the truck bed for securing the left and right side panels and the left and right elongating side panels to the left and right side walls of the truck bed.

The rear shell, front shell, left and right side panels may be fabricated from carbon fiber, aluminum, fiberglass, plastic or steel.

The front shell may be pivoted to an angle of about 270 degrees to allow the front shell to hang down when loading and unloading the truck bed.

The left and right latches may be removably attached to left and right standard latch receivers of the truck bed.

The tailgate may further comprise a cover for a pivot joint between the front and rear shells.

In another aspect, a method of elongating a bed length of a truck is disclosed. The method may comprise the steps of providing a tailgate for a bed of a truck and pivotally attaching a lower edge of the rear shell to the lower rear edge of the truck bed. In the providing step of the method, the tailgate may comprise a rear shell, a front shell, left and right side panels and left and right latches. The rear shell may be sized and configured to fit between left and right sidewalls of the truck bed. The rear shell may be pivotally attached to a lower rear edge of the truck bed. The front shell may be pivotally attached to an upper edge of the rear shell. The front shell may be pivoted greater than 180 degrees when the front shell is disposed generally parallel to the rear shell. The left and right side panels may be pivotally attached to left and right side portions of the front shell. The left and right latches may be attached to the left and right side panels and the left and right sidewalls of the truck bed to mitigate unwanted movement of the rear shell, front shell and the left and right panels during forward movement of the truck.

The method may further comprise the step of rotating the tailgate so that the front and rear shells are generally parallel to a ground. The method may also further comprise the steps of rotating the front shell about an upper edge of the rear shell so that the front and rear shells are about 90 degrees from each other; rotating the left and right side panels toward the left and right sidewalls of the truck bed; and securing the left and right side panels to the left and right sidewalls of the truck bed with the left and right latches.

The method may also further comprise the steps of elongating telescoping first and second panels of the front shell to elongate a length of the truck bed; pivoting left and right elongating side panels from the left and right side panels; and securing the left and right elongating side panels to the left and right sidewalls of the truck bed with the left and right latches.

In another aspect, a tailgate extender for a bed of a truck is disclosed. The tailgate extender may comprise first, sec-

3

ond and third driver-side vertical panels and first, second and third passenger-side vertical panels.

The first driver side vertical panel may be pivotally attached to a driver side sidewall of the bed of the truck. The second driver side vertical panel may be pivotally attached to the first driver side vertical panel. The third driver side vertical panels may be pivotally attached to the second driver side vertical panel. The first, second and third driver side vertical panels may be stacked adjacent to each other and disposed in a cavity formed at a rear inner portion of the driver side sidewall of the bed of the truck. The first driver side vertical panel may be pivoted so as to be parallel to a driver side edge of the tailgate. The second and third driver side vertical panels may be pivoted so as to be parallel to a back edge of the tailgate.

The first passenger side vertical panel may be pivotally attached to a passenger side sidewall of the bed of the truck. The second passenger side vertical panel may be pivotally attached to the first passenger side vertical panel. The third passenger side vertical panels may be pivotally attached to the second passenger side vertical panel. The first, second and third passenger side vertical panels may be stacked adjacent to each other and disposed in a cavity formed at a rear inner portion of the passenger side sidewall of the bed of the truck. The first passenger side vertical panel may be pivoted so as to be parallel to a passenger side edge of the tailgate. The second and third passenger side vertical panel may be pivoted so as to be parallel to a back edge of the tailgate.

The tailgate extender may further comprising a replacement tailgate defining an upper surface with a groove for receiving the second and third driver-side and passenger side vertical panels. The groove may be parallel with the back edge of the replacement tailgate.

The second and third driver side and passenger side vertical panels may have flexible strips at a bottom end of the second and third driver side and passenger side vertical panels which are receivable in the groove formed in the replacement tailgate.

In another aspect, a method of extending a truck bed of a truck is disclosed. The method may comprise the steps of providing driver-side first, second and third vertical panels which are stacked upon each other and disposed in a driver-side cavity formed by a driver-side sidewall of the truck bed; providing a passenger-side first, second and third vertical panels which are stacked upon each other and disposed in a passenger-side cavity formed by a passenger-side sidewall of the truck bed; pivoting a tailgate to an opened position so that an upper surface of the tailgate is generally coplanar with an upper surface of the truck bed; pivoting the driver side first, second and third vertical panels out from the driver side cavity so that the driver side first vertical panel is parallel with a driver side edge of the tailgate; pivoting the passenger side first, second and third vertical panels out from the passenger side cavity so that the passenger side first vertical panel is parallel a passenger side edge of the tailgate; and pivoting the driver side and passenger side second and third vertical panels away from the driver side and passenger side first vertical panels so that the second and third vertical panels are parallel to a back edge of the tailgate.

In the method, the step of pivoting the driver side and passenger side second and third vertical panels away from the driver side and passenger side first vertical panels may include the steps of pivoting the driver side third vertical panel away from the driver side second vertical panel; and

4

pivoting the passenger side third vertical panel away from the passenger side third vertical panel.

In the method, the step of pivoting the driver side and passenger side second and third vertical panels away from the driver side and passenger side first vertical panels may also include the step of disposing weather stripping attached to bottom portions of the driver side and passenger side second and third vertical panels in a groove formed in the upper surface of the tailgate.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features and advantages of the various embodiments disclosed herein will be better understood with respect to the following description and drawings, in which like numbers refer to like parts throughout, and in which:

FIG. 1 is a perspective view of a truck with a replacement tailgate installed on a bed of the truck;

FIG. 2 illustrates a cover of the tailgate shown in FIG. 1 pivoted outward;

FIG. 3 illustrates the tailgate shown in FIG. 2 pivoted downward;

FIG. 4 illustrates a front shell of the tailgate pivoted upward so that the front shell and a rear shell are at a 90° pivoting angle;

FIG. 5 illustrates the front shell of the tailgate pivoted so that the pivoting angle is at 270° between the front shell and the rear shell;

FIG. 6 illustrates the left and right side panels being pivoted outward when the rear shell is 90° with respect to the front shell;

FIG. 7 illustrates the left and right side panels pivoted outward;

FIG. 8 illustrates latches of the left and right side panels engaging standard latch receivers of the truck bed;

FIG. 9 illustrates first and second telescoping panels of the rear shell;

FIG. 10 illustrates the front shell of the tailgate pivoted upward so that the front shell and the rear shell are at a 90° pivoting angle;

FIG. 11 illustrates the front shell of the tailgate pivoted so that the pivoting angle is about 270° between the front shell and the rear shell;

FIG. 12 illustrates the front shell pivoted back to the 90° pivoting angle after objects are placed in the truck bed;

FIG. 13 illustrates the left and right side panels being pivoted outward;

FIG. 14 illustrates left and right elongating side panels pivoted outward and secured to standard receivers of the truck bed with latches;

FIG. 15 illustrates another embodiment of the pick up truck bed elongator;

FIG. 16 illustrates the elongator of FIG. 15 with a tailgate in an opened position;

FIG. 17 illustrates the elongator of FIG. 15 with first, second and third vertical panels being traversed to an expanded position;

FIG. 18 illustrates the elongator of FIG. 15 with the first and second vertical panels traversed to the expanded position;

FIG. 19 illustrates the elongator of FIG. 15 with the third vertical panel being traversed to the expanded position; and

FIG. 20 illustrates the elongator of FIG. 15 with the first through third vertical panels traversed to the expanded position.

DETAILED DESCRIPTION

Referring now to the drawings, a replacement tailgate 10a for a bed 12 of the truck 14 for the purpose of elongating the

5

pickup truck is shown. The tailgate **10a** may replace the factory tailgate and enable the user to elongate the factory length **16** of the truck bed **12** of the truck **14**. The tailgate **10a** can elongate the factory length **16** of the truck bed **12** about a height **18** of the truck bed **12** or an elongated length **20** (see FIG. **11**). The tailgate **10**, **10a** can also be secured to standard factory latching mechanisms of the factory installed truck bed so that no or little modification to the truck bed **12** is necessary in order to retrofit the truck **14** with the tailgate **10**. Alternatively, the factory tailgate may be used to elongate the factory length **16** of the truck bed **12** of the truck **14**.

Referring now the FIGS. **1-8**, the tailgate **10** is shown as being deployed to elongate the length **16** of the truck bed **12** to the height **18** of the truck bed **12**. In particular, the tailgate **10** has cover **22**. The cover **22** is disposed on top of upper ends **24**, **26** of front and rear shells **28**, **30** of the tailgate **10**. The cover **22** prevents objects from being inadvertently disposed between the front and rear shells **28**, **30**. The front shell **28** functions as the tailgate when the factory length **16** of the truck **12** is elongated by the height **18** of the truck bed **12**, as shown in FIG. **8**. The rear shell **30** functions as a bottom support for elongating the length **16** so that longer objects **34** can be placed in the truck bed **12** and secured therein by the tailgate **32**. Pivoting the cover **22** about the upper end **26** of the rear shell **30** may enable the front shell **28** to be pivoted about the rear shell **30**.

After pivoting the cover **22** to the open position as shown in FIG. **2**, the user may release the tailgate **10** from the left and right side walls **36**, **38** to lower the front and rear shells **28**, **30** to elongate the factory length **16** of the truck bed **12**. As discussed above, the cover **22** may be attached and configured to the tailgate **10** so that pivoting of the cover **22** to the open position enables pivoting of the front shell **28** about the rear shell **30**. In this regard, the cover **22** can be pivoted to the open position either before or after the tailgate **10** is traversed to the down position, as shown in FIG. **3**. Moreover, it is also contemplated that the ability of the front and rear shells **28**, **30** to be pivoted about each other can be independent of the position of the cover **22**. The cover **22** can be held in the closed position, as shown in FIG. **1** or in the open position as shown in FIG. **2** with a detent or other latching mechanism.

Once the tailgate **10** is pivoted downward, the front shell **28** can be pivoted upward as shown in FIG. **4**. The pivoting angle **40** can be limited to between about 90° and about 270° (see FIG. **5**), as shown in FIGS. **4** and **5**. The pivoting angle **40** can be limited by way of a detent or other mechanism known in the art or developed in the future. When the front shell **28** is pivoted 270° , the user can slide objects **34** into the bed then lift the front shell **28** upward to trap the objects **34** in the truck bed **12**, as shown in FIG. **6**.

The front shell **28** may have a height **42** (see FIG. **4**) equal to about the height **18** of the tailgate **10**. Alternatively, the height **42** of the front shell **28** may be greater than or less than the height **18** but is preferably about equal to the height **18** of the tailgate **10**.

As shown in FIG. **7**, left and right side panels **44**, **46** can be rotated outward and secured to the left and right side walls **36**, **38** of the truck bed **12** with the latching mechanism **48**. The latching mechanism **48** may be secured to the standard receivers on truck beds so that no or little modification to the truck bed **12** is needed. By securing the latching member **48** to the standard receivers on the truck bed **12**, the pivoting angle **40** of the front shell **28** is locked to 90° . Also, the elongated length **20** is set to the height **18** of the tailgate **10**. Objects **34** placed within the truck bed **12** remain secured therein by way of the front shell **28** and the left and

6

right side panels **44**, **46**. The left and right side panels **44**, **46** may remain in the un-deployed state as shown in FIGS. **4** and **5**. By way of example and not limitation, the left and right side panels **44**, **46** and the front shell **28** may have magnets and/or detents that hold the left and right side panels **44**, **46** against the front shell **28**. Other mechanisms are also contemplated such as detents, latches, etc.

In a further feature, the tailgate **10** may be used to elongate the factory length **16** of the truck bed **12** greater than the height and up to an elongated length **20**. To this end, referring now to FIGS. **9-14** the rear shell **30** may be fabricated from telescoping first and second telescoping panels **50**, **52**. By extending the telescoping first and second panels **50**, **52**, the truck bed **12** can be elongated by length **54** (see FIG. **10**) which is greater than the height **18**. The second telescoping panel **52** may be traversed between the retracted position, shown in FIG. **3** or the elongated position, shown in FIG. **10**. The second telescoping panel **52** may be retained in the retracted position or elongated position by way of a detent or other mechanism known in the art or developed in the future.

Once the second telescoping panel **52** is traversed to the expanded position as shown in FIG. **10**, the front shell **28** may be pivoted downward so that the front shell **28** hangs downward as shown in FIG. **11**. In this way, objects **34** can be slid onto or off of the truck bed **12**. Once objects **34** are placed in the truck bed **12**, the user can traverse the front shell **28** so that the front shell **28** is 90° with respect to the rear shell **30**, shown in FIG. **12**. The left and right side panels **44**, **46** can be rotated outward as shown in FIG. **13**. Moreover, left and right elongating panels **56**, **58** can also be rotated to close the gap **60** between the left and right side panels **44**, **46** and the left and right side walls **36**, **38** of the truck bed **12**. Once the latches **60**, **62** are secured to the receivers, objects **34** placed on the truck bed cannot slip out of the truck bed **12** due to the front shell **28**, left and right side panels **44**, **46** and the left and right elongating panels **56**, **58**.

The front and rear shells **20**, **30**, left and right side panels **44**, **46** and the left and right elongating panels **56**, **58** may be fabricated from a variety of materials including but not limited to carbon fiber, steel, fiberglass, plastic, aluminum, and other materials known in the art or developed in the future.

The tailgate **10** described herein has been describe as a replacement to a factory tailgate. However, it is also contemplated that the tailgate may be offered as original equipment from the factory or manufacturer.

Referring now to FIGS. **15-20**, a second embodiment of the apparatus and device for extending the factory length **16** (see FIG. **16**) of the truck bed **12** of the truck **14** is shown. In particular, the replacement tailgate **10a** may be attached to the truck bed **12** by attaching the tailgate **10a** to the standard attachment mechanisms provided in the truck **14**. By way of example and not limitation, the tailgate **10a** may be pivotally attached to a rear portion of the truck bed **12**. The tailgate **10a** may pivot about pivot axis **70**. Preferably, the pivot motion of the tailgate **10a** may be limited to 90° as shown in FIGS. **15** and **16**. The tailgate **10a** when in the vertical orientation may be in the locked position and unlocked only when the user grips the handle **72** and releases the latching mechanism between the tailgate **10a** and the factory latching mechanisms in the side walls of the truck bed **12** of the truck **14**. When the tailgate **10a** is pivoted downward as shown in FIG. **16**, the tailgate **10a** and more particularly an upper surface **76** of the tailgate **10a** may be coplanar with an upper surface **74** of the truck bed **12** so that

the tailgate **10a** now extends the length **16** of the truck bed **12** plus the tailgate **10a**. Objects **34** placed within the truck bed **12** may be retained therein with a plurality of driver-side vertical panels **78** and passenger-side vertical panels **80** which are stacked, folded, and stored into cavities **82**, **84** formed by the side walls **36**, **38** and the top ledge **86**, **88** of the left and right side walls **36**, **38**.

The passenger-side vertical panels **80a-c** and the driver-side vertical panels **78a-c** may be pivoted out as shown in FIGS. **17-20**. In particular, panels **78a**, **80a** may pivot around 90° about vertical pivot axes **90**, **92**. The vertical panels **78a**, **80a** may extend out until the vertical panels **78a**, **80a** are parallel to left and right side edges **94**, **96** of the tailgate **10a**, shown in FIG. **18**. The vertical panels **78a**, **80a** may be secured in this position by means known in the art or developed in the future. By way of example and not limitation, the vertical panels **78a**, **80a** may have detents or other latching mechanisms that may be used to attach the vertical panels **78a**, **80a** to the tailgate **10a**.

The panels **78b**, **80b** may be pivoted until the panels **78b**, **80b** are generally parallel with the back edge **98** of the tailgate **10a**. The panels **78b** and **80b** may be pivoted about vertical pivot axes **104**, **106**. Likewise, the vertical panels **78c**, **80c** may be pivoted to close the opening **108** as shown in FIG. **20**. The vertical panels **78c**, **a-c** may be pivoted about vertical pivot axes **110**, **112**. The bottom edge portions **100** of the panels **78b**, **c** and **80b**, **c** may have a rubberized weather stripping **102**. The weather stripping **102** may be received into a groove **104** formed in the upper surface **76** of the tailgate **10a**. The panels **78b**, **c** and panels **80b**, **c** may be held in position by way of latching mechanisms known in the art or developed in the future. By way of example and not limitation, these latching mechanisms include but are not limited to detents, over center latches, etc. Moreover, the disposition of the weather strip **102** of the panels **78b**, **c** and **80b**, **c** also help to retain the panels **78b**, **c**, **80b**, **c** parallel to the back edge **98** of the tailgate **10a**. The two vertical panels **78c**, **80c** may also be latched together with the latching mechanism known in the art or developed in the future. In this manner, objects **34** placed in the truck bed may roll around in the truck bed **12** but will not roll out of the truck bed **12** because the objects **34** are blocked by the vertical panels **78a**, **b**, **c** and panels **80a**, **b**, **c**.

In a variant of the second embodiment of the tailgate **10a**, the original factory tailgate may be utilized in conjunction with the left and right vertical panels **70a**, **b**, **c** and vertical panels **80a**, **b**, **c**. To this end, the hinge that allows the panels **78a**, **80a** to be pivoted about vertical pivot axes **90**, **92** may be locked in the deployed state as shown in FIG. **18**. Likewise, the hinge that enables the panels **78b**, **80b** to pivot about vertical pivot axes **104**, **106** may be locked in the deployed state as shown in FIG. **19**. Optionally, the hinge that enables the panels **78c**, **80c** to pivot about vertical axes **110**, **112** may be locked in the deployed state as shown in FIG. **20** or alternatively the panels **78c** and **80c** may freely rotate out the vertical pivot axes **110**, **112** and be locked in the deployed state as shown in FIG. **20** by way of the latching mechanism that secures the panels **78c** to **80c** and vice versa.

The above description is given by way of example, and not limitation. Given the above disclosure, one skilled in the art could devise variations may be within the scope and spirit of the invention disclosed herein, including various ways of securing the panels to the factory receiver of the factory tailgate of the truck bed. Further, the various features of the embodiments disclosed herein can be used alone, or in varying combinations with each other and are not intended

to be limited to the specific combination described herein. Thus, the scope of the claims is not to be limited by the illustrated embodiments.

What is claimed is:

1. A tailgate extender for a bed of a truck, the tailgate extender comprising:

first, second and third driver-side vertical panels, the first driver side vertical panel pivotally attached to a driver side sidewall of the bed of the truck, the second driver side vertical panel pivotally attached to the first driver side vertical panel, the third driver side vertical panels pivotally attached to the second driver side vertical panel wherein the first, second and third driver side vertical panels are stackable adjacent to each other and disposable in a cavity formed at a rear inner portion of the driver side sidewall of the bed of the truck, the first driver side vertical panel being pivotable so as to be parallel to a driver side edge of a tailgate, the second and third driver side vertical panel being pivotable so as to be parallel to a back edge of the tailgate;

first, second and third passenger-side vertical panels, the first passenger side vertical panel pivotally attached to a passenger side sidewall of the bed of the truck, the second passenger side vertical panel pivotally attached to the first passenger side vertical panel, the third passenger side vertical panels pivotally attached to the second passenger side vertical panel wherein the first, second and third passenger side vertical panels are stackable adjacent to each other and disposable in a cavity formed at a rear inner portion of the passenger side sidewall of the bed of the truck, the first passenger side vertical panel being pivotable so as to be parallel to a passenger side edge of the tailgate, the second and third passenger side vertical panel being pivotable so as to be parallel to the back edge of the tailgate.

2. The tailgate extender of claim 1 further comprising a replacement tailgate defining an upper surface with a groove for receiving the second and third driver-side and passenger side vertical panels.

3. The tailgate extender of claim 2 wherein the groove is parallel with the back edge of the replacement tailgate.

4. The tailgate extender of claim 3 wherein the second and third driver side and passenger side vertical panels have flexible strips at a bottom end of the second and third driver side and passenger side vertical panels which are receivable in the groove formed in the replacement tailgate.

5. A method of extending a truck bed of a truck, the method comprising the steps of:

providing driver-side first, second and third vertical panels which are stacked upon each other and disposed in a driver-side cavity formed by a driver-side sidewall of the truck bed;

providing a passenger-side first, second and third vertical panels which are stacked upon each other and disposed in a passenger-side cavity formed by a passenger-side sidewall of the truck bed;

pivoting a tailgate to an opened position so that an upper surface of the tailgate is generally coplanar with an upper surface of the truck bed;

pivoting the driver side first, second and third vertical panels out from the driver side cavity so that the driver side first vertical panel is parallel with a driver side edge of the tailgate;

pivoting the passenger side first, second and third vertical panels out from the passenger side cavity so that the passenger side first vertical panel is parallel a passenger side edge of the tailgate;

pivoting the driver side and passenger side second and third vertical panels away from the driver side and passenger side first vertical panels so that the second and third vertical panels are parallel to a back edge of the tailgate.

5

6. The method of claim 5 wherein the step of pivoting the driver side and passenger side second and third vertical panels away from the driver side and passenger side first vertical panels includes the steps of:

pivoting the driver side third vertical panel away from the driver side second vertical panel;

10

pivoting the passenger side third vertical panel away from the passenger side third vertical panel.

7. The method of claim 5 wherein the step of pivoting the driver side and passenger side second and third vertical panels away from the driver side and passenger side first vertical panels includes the step of:

15

disposing weather stripping attached to bottom portions of the driver side and passenger side second and third vertical panels in a groove formed in the upper surface of the tailgate.

20

* * * * *